## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization

International Bureau



# ) (1814 - 19<del>94 - 1984 - 1984 - 1984 - 1984 - 1984 - 1984 - 1</del>7 (1) (1984 - 1984 -

(43) International Publication Date 15 July 2004 (15.07.2004)

PCT

#### (10) International Publication Number WO 2004/058888 A1

(51) International Patent Classification7: 67/00

C08L 59/04.

(21) International Application Number:

PCT/KR2003/002911

(22) International Filing Date:

30 December 2003 (30.12.2003)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data: 10-2002-0088060

> 31 December 2002 (31.12.2002) KR

- (71) Applicant (for all designated States except US): KOLON INDUSTRIES, INC. [KR/KR]; 1-23 Byeoryang-dong, Gwacheon-si, 427-709 Gyeonggi-do (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PARK, Yong-Seon [KR/KR]; 212 Gongdan-dong, Gumi-si, 730-030 Gyeongsangbuk-do (KR). SHIN, Moon-Cheul [KR/KR]; 134-7, Beomeo-2-dong, Suseong-gu, 706-818 Daegu

(KR). LIM, Mok-Keun [KR/KR]; 212 Gongdan-dong, Gumi-si, 730-030 Gyeongsangbuk-do (KR).

- (74) Agent: RO, Wan-Goo; 3Fl., Jaegyeong Bldg., 1670-12, Seocho-1-dong, Seocho-gu, Seoul 137-881 (KR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TOUGHENED POLYOXYMETHYLENE RESIN COMPOSITION

(57) Abstract: Disclosed is a toughened polyoxymethylene resin composition, including a polyoxymethylene resin, a polyether-ester block copolymer derived from copolymerization of a hard segment including a dicarboxylic acid component and a glycol component and a soft segment including a poly(tetramethylene oxide)terephthalate unit, and a modified polyethylene polymer, which is advantageous in terms of high mechanical properties with an Izod notch impact strength of 10 kg-cm/cm or more and a tensile strength of 550 kg/cm<sup>2</sup> or more, while maintaining a dot impact strength of 5 J or more. Hence, molded articles using the above resin composition are improved in resistance to impact, wear and friction, and thus, can be usefully applied to gears or bearings having low noise.